

O-RING ASSEMBLY GRIPPER, OUTER

INSTALLATION SIZE GS1015

1

Installation size GS1015 / O-ring assembly gripper, outer / pneumatic / Grippers

▶ PRODUCT SPECIFICATIONS



▶ INCLUDED IN DELIVERY



Mounting block

KB8K



Centering Disc

DST60800

▶ RECOMMENDED ACCESSORIES



Straight Fittings - Quick Connect Style

GV1-8X8




Magnetic field sensor Angled Cable 5 m

MFS103KHC




Magnetic field sensor Angled Cable 0,3 m - Connector M8

MFS103SKHC




Plug-in connector Angled Cable 5m - Socket M8 (female)

KAW500



Plug-in connector Straight Cable 5m - Socket M8 (female)

KAG500




Inductive proximity switch - Cable 5 m

NJ8-E2



Inductive proximity switch - Connector M8

NJ8-E2S



Ejector Jaws Aluminium

UB1015-3



Expanding Jaws Steel

UB1015-4



Plug-in connector customizable Straight - Connector M8

S8-G-3

► Technical Data*	
Order no.	GS1015-B
Opening stroke adjustable per jaw min. [mm]	1.6
Opening stroke adjustable per jaw max. [mm]	10
Stripping stroke [mm]	15
Opening force [N]	1450
Recommended O-ring diameter min. [mm]	40
Recommended O-ring diameter max. [mm]	150
Number of gripping jaws [Quantity]	10
Closing time [s]	0.05
Opening time [s]	0.05
Repetition accuracy +/- [mm]	0.05
Operating pressure min. [bar]	3
Operating pressure max. [bar]	8
Operating temperature min. [°C]	5
Operating temperature max. [°C]	80
Weight [kg]	5.4

*All data measured at 6 bar

